## NSN 5905-01-527-9262

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-527-9262
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -30.0/+30.0
Electrical Resistance:
38.300 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reactance Characteristic:
Inductive
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
Between 0.204 inches and 0.328 inches
Body Diameter:
Between 0.065 inches and 0.105 inches
Body Length:
Between 0.538 inches and 0.662 inches
Body Width:
Between 0.272 inches and 0.396 inches
Body Height:
Between 0.289 inches and 0.351 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 0.434 inches and 0.454 inches
Power Dissipation Rating In Watts:
5.000 free air
Terminal Width:
0.085 inches
End Application:
F15 aircraft aircraft, eagle f15

**Mounting Hole Size:** 

Between 0.088 inches and 0.098 inches

## NSN 5905-01-527-9262

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Unpackaged Unit Weight:
3.3 grams
Style Designator:
Axial terminal (s)
Test Data Document:
81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349 - mil-prf-39007/9 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A001a0
Mil-std (military Standard):
Mil-prf-39007 spec.