NSN 5905-01-528-8660

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-528-8660

Section Quantity:
1
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
28.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 230.0 and 250.0
Center To Center Distance Between Terminals:
0.183 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
4
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
2500.0 ohms single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Switch Current Type And Rating In Amps:
0.000125 dc
Special Features:
White molded thermoplastic housing: nickel plated brass shaft: cermet element

NSN 5905-01-528-8660

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0