## NSN 5905-01-530-4826

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-530-4826

Sastian Oversites
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
2.375 inches
First Flat Length:
0.375 inches
Flat Height:
0.219 inches
Body Diameter:
3.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Mounting Bushing Length:
0.937 inches
Body Length:
1.500 inches
Overall Diameter:
3.156 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
End Application:
8s-842/g shelter
Screw Thread Diameter:
0.162 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:

25.0 ohms single section

## NSN 5905-01-530-4826

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## **Power Dissipation Rating Per Section In Watts:** 100.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

**Special Features:** 

Power rheostat, 100 watt

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A002a0