NSN 5905-01-532-3815

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-532-3815

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-300.0/+300.0
Electrical Resistance:
220.000 ohms
Resistance Tolerance In Percent:
-5.000/ + 5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Inclosure Method:
Uninclosed
Terminal Type:
Wrap around
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
Between 0.26 millimeters and 0.64 millimeters
Body Length:
Between 3.0 millimeters and 3.4 millimeters
between 3.0 minimeters and 3.4 minimeters
Body Width:
Body Width:
Body Width: Between 1.47 millimeters and 1.73 millimeters
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height:
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts:
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features:
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts Style Designator:
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts Style Designator: Termination pad each end
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts Style Designator: Termination pad each end Shelf Life:
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts Style Designator: Termination pad each end Shelf Life: N/a
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts Style Designator: Termination pad each end Shelf Life: N/a
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts Style Designator: Termination pad each end Shelf Life: N/a Unit Of Measure:
Body Width: Between 1.47 millimeters and 1.73 millimeters Body Height: Between 0.71 millimeters and 0.97 millimeters Power Dissipation Rating In Watts: 0.250 free air Special Features: Reliability per 1000.0 hours; continuous working voltage not to exceed 100.0 volts Style Designator: Termination pad each end Shelf Life: N/a Unit Of Measure: Demilitarization: