# NSN 5905-01-532-6735

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-532-6735

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-5.0/+5.0 first temp coefficient

#### **Electrical Resistance:**

9.650 kilohms

# **Resistance Tolerance In Percent:**

-0.010/+0.010

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

+25.0/+125.0 temp range of first temp coefficient

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

# Mil-std-1276 Wire Lead Type Designator:

```
С
```

# **Reliability Indicator:**

Established

# Reliability Failure Rate Level In Percent:

0.010

#### **Terminal Length:**

Between 0.875 inches and 1.875 inches

#### **Body Length:**

0.336 inches

#### **Body Width:**

Between 0.290 inches and 0.320 inches

#### **Body Height:**

Between 0.095 inches and 0.120 inches

#### **Power Dissipation Rating In Watts:**

0.300 free air

# Style Designator:

Terminals one edge

# Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-55182/9 government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5905-01-532-6735

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.

