NSN 5905-01-533-3416

Film Fixed Resistor - Page 1 of 2

-100.0/+100.0

5.600 kilohms

-1.000/+1.000

Electrical Resistance:

Resistance Tolerance In Percent:



View Online at https://aerobasegroup.com/nsn/5905-01-533-3416

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+150.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.500 inches
Body Diameter:
0.090 inches
Body Length:
0.250 inches
Power Dissipation Rating In Watts:
0.250 free air
Unpackaged Unit Weight:
0.500 grams
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-prf-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-prf-39017/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5905-01-533-3416

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39017 spec.