NSN 5905-01-534-2413

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-534-2413

Reliability Indicator: Not established Body Length: 0.064 inches Body Width: 0.122 inches Body Height: 0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section Resistance Tolerance Per Section In Percent:
Not established Body Length: 0.064 inches Body Width: 0.122 inches Body Height: 0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Body Length: 0.064 inches Body Width: 0.122 inches Body Height: 0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
0.064 inches Body Width: 0.122 inches Body Height: 0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Body Width: 0.122 inches Body Height: 0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
0.122 inches Body Height: 0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Body Height: 0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
0.122 inches Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Actuator Type: Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Flush drive with slot-hole Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Electrical Resistance Per Section: 1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
1000.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
-250.0/+250.0 single section Power Dissipation Rating Per Section In Watts: 0.15 free air single section
Power Dissipation Rating Per Section In Watts: 0.15 free air single section
0.15 free air single section
-
Resistance Tolerance Per Section In Percent:
-25.0/+25.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0