NSN 5905-01-535-1343

Section Quantity:

Cylindrical bushing mounted

Between 0.245 inches and 0.255 inches

Reliability Indicator:

Not established First Flat Length:

Body Style:

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-535-1343

Flat Height:
0.094 inches
Body Diameter:
Between 0.495 inches and 0.505 inches
Shaft Diameter:
0.124 inches
Shaft Length:
Between 0.690 inches and 0.710 inches
Mounting Bushing Length:
Between 0.302 inches and 0.322 inches
Body Length:
Between 0.300 inches and 0.310 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Terminal Type And Quantity:
3 turret

NSN 5905-01-535-1343

Precision Wire Wound Variable Resistor - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0