NSN 5905-01-535-8792

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-535-8792

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -25.0/+25.0 Electrical Resistance: 1.870 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator:
Electrical Resistance: 1.870 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
1.870 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
-5.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Established Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Reliability Failure Rate Level In Percent: 0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
0.010 Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Body Diameter: Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Between 0.160 inches and 0.328 inches Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Body Length: Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Between 0.500 inches and 0.875 inches Power Dissipation Rating In Watts: 0.500 free air
Power Dissipation Rating In Watts: 0.500 free air
0.500 free air
Style Designator:
, g'''a'' '
Axial terminal each end
Shelf Life:
N/a
N/a Unit Of Measure:
Unit Of Measure:
Unit Of Measure: Demilitarization:
Unit Of Measure: Demilitarization: No