

View Online at <https://aerobasegroup.com/nsn/5905-01-537-9647>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-30.0/+30.0

**Electrical Resistance:**

6.650 kilohms

**Resistance Tolerance In Percent:**

-1.000/+1.000

**Ambient Temperature In Deg Celsius At Full Rated Power:**

25.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

275.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0/+275.0

**Inclosure Method:**

Encased

**Terminal Type:**

Tab, solder lug

**Reactance Characteristic:**

Inductive

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.010

**Terminal Length:**

0.438 inches

**Body Length:**

1.062 inches

**Body Width:**

0.531 inches

**Body Height:**

0.562 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

0.719 inches

**Power Dissipation Rating In Watts:**

8.000 free air

**Terminal Width:**

0.140 inches

**End Application:**

Los angeles class ssn (688); control, mcc alarm; ssgn trident class master control center security and ventilation alarm monitoring panel

**Mounting Hole Size:**

0.125 inches

**Product Name:**

Resistor, fixed, wire wound

**Style Designator:**

Axial terminal (s)

**Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-r-39009/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A001a0