NSN 5905-01-538-2152

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-538-2152 **Section Quantity: Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Shaft Diameter:** Between 0.100 inches and 0.130 inches **Shaft Length:** Between 0.036 inches and 0.070 inches **Body Length:** 1.250 inches **Body Width:** Between 0.300 inches and 0.330 inches **Body Height:** 0.190 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 500.0 ohms single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 70.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Special Features:** On qpl for rj12 style of mil-prf-22097; effectove travel: 22 turns, nom; rotational life: 200 cycles; terminal finish: 90 percent tin, 10 percent lead-plated **Terminal Type And Quantity:** 3 wire lead Shelf Life:

--

N/a

Unit Of Measure:

NSN 5905-01-538-2152

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



_		••	• •				
n	em	ш	112	riz	2 †1	n	٠.

No

Fiig:

A002a0

Mil-std (military Standard):

Mil-prf-22097 spec.