## NSN 5905-01-538-4319

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-538-4319

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.245 inches
Shaft Diameter:
0.090 inches
Shaft Length:
0.060 inches
Body Length:
0.395 inches
Body Width:
0.240 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
End Application:
Virginia class submarine; assembly, can no. 1, rack 2/3
Terminal Location:
Rear end
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Features Provided:
Hermetically sealed
Electrical Resistance Per Section:
25.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100 0/+100 0 single section

0.5 free air single section

**Power Dissipation Rating Per Section In Watts:** 

## NSN 5905-01-538-4319

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Special Features:** 

Multiturn; cermat; industrial; mechanical stops: wiper idles; terminal finish: 90 percent tin, 10 percent lead-plated

**Supplementary Features:** 

Inavy: potentiometer; cage 80294: 3299 - 3/8 in. Square trimming potentiometer

**Terminal Type And Quantity:** 

3 pin

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0