NSN 5905-01-541-0259

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-541-0259

Section Quantity:
1
•
Body Style:
Cylindrical servo mounted
Reliability Indicator: Not established
Pilot Diameter:
0.7500 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.781 inches
Undercut Width:
0.0570 inches
Body Diameter:
0.906 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.500 inches
Body Length:
0.810 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
End Application:
7647405 (53711) 18h mo (1) subis eyepiece bx unit 2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section

-10.0/+10.0 single section

Resistance Tolerance Per Section In Percent:

NSN 5905-01-541-0259

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:

Altered item: begin with (81349) rq090ab13dc202 and add 0.015 in. X 45 deg. Chamfer to shaft, 0.215-0.220 in. From body; procuring agency is responsible for the alteration

Supplementary Features:

length is 1.000 inch; 1 watt; single-turn

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0