

View Online at <https://aerobasegroup.com/nsn/5905-01-541-0259>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0570 inches

Body Diameter:

0.906 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

0.810 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

End Application:

7647405 (53711) 18h mo (1) subis eyepiece bx unit 2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

2.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Special Features:

Altered item: begin with (81349) rq090ab13dc202 and add 0.015 in. X 45 deg. Chamfer to shaft, 0.215-0.220 in. From body; procuring agency is responsible for the alteration

Supplementary Features:

length is 1.000 inch; 1 watt; single-turn

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0