## NSN 5905-01-544-1359

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-544-1359

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -50.0/+50.0 first temp coefficient  |
| Electrical Resistance:  |
| 15.000 kilohms  |
| Resistance Tolerance In Percent:  |
| -1.000/+1.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 25.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 275.0   |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 1.375 inches and 1.625 inches   |
| Body Diameter:  |
| Between 0.084 inches and 0.134 inches   |
| Body Length:  |
| Between 0.283 inches and 0.343 inches   |
| Power Dissipation Rating In Watts:  |
| 1.000 free air  |
| Terminal Width:   |
| Between 0.023 inches and 0.027 inches   |
| Product Name:   |
| Type ms power film resistor   |
| Special Features:   |
| Constructed with micronox resistance films bonded to a high strength solid ceramic core; nickel alloy end caps and axial leads;         |
| encapsulated with a high temperature silicone conformal coating; lead material is nickel clad copper with thin gold plating, solderable |
| Style Designator:   |
| Axial terminal each end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |