NSN 5905-01-544-5958

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-544-5958 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** Between 0.183 inches and 0.213 inches **Shaft Diameter:** Between 0.160 inches and 0.180 inches **Shaft Length:** Between 0.030 inches and 0.050 inches **Body Length:** Between 0.230 inches and 0.270 inches **Body Width:** Between 0.155 inches and 0.185 inches **Body Height:** Between 0.250 inches and 0.290 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Center To Center Distance Between Terminals:** Between 0.180 inches and 0.220 inches **End Application:** Ug3500te **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 2.0 kilohms single section **Center To Center Distance Between Center Terminal And Outside Terminal:** Between 0.090 inches and 0.110 inches **Power Dissipation Rating Per Section In Watts:** 0.2 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Terminal Type And Quantity:** 3 pin

Shelf Life:

N/a

NSN 5905-01-544-5958

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| | • - | | | |
|----|-----|------|---------|---|
| In | ıŧ | ()t | Measure | • |
| | | | | |

--

Demilitarization:

No

Fiig:

A002a0