NSN 5905-01-544-7270

Section Quantity:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-544-7270

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.825 inches
Shaft Diameter:
0.250 inches
Shaft Length:
Between 0.412 inches and 1.212 inches
Mounting Bushing Length:
0.313 inches
Body Length:
1.000 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
End Application:
7519653 (53711) ty8k mo (4) peris assembly
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Terminal Type And Quantity:
3 eyelet
Departure From Cited Document:
Hybrid multi-turn potentiometer

NSN 5905-01-544-7270

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0