Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-547-0054

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

### **Body Diameter:**

6.4 millimeters

#### Shaft Diameter:

3.1 millimeters

#### Shaft Length:

16.0 millimeters

#### Mounting Bushing Length:

9.5 millimeters

## Body Length:

16.0 millimeters

#### Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

### End Application:

Consolidated avionic accessories; control indicator, a

### Screw Thread Diameter:

0.250 inches

### Screw Thread Series Designator:

Unf

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Rear end

#### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

10.0 kilohms single section

#### **Power Dissipation Rating Per Section In Watts:**

1.5 free air single section

## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### **Special Features:**

High power rating: 1.5 watt at 70 degrees c; variation law: cw log; cermet

# Terminal Type And Quantity:

3 tab, solder lug

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0