NSN 5905-01-550-3728

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-550-3728 **Electrical Resistance:** 20.000 kilohms **Resistance Tolerance In Percent:** -5.000/+5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 110.0 **Inclosure Method:** Encased **Terminal Type:** Tab, solder lug **Reactance Characteristic:** Noninductive **Reliability Indicator:** Not established **Terminal Length:** 10.0 millimeters **Body Length:** 29.0 millimeters **Body Width:** 16.5 millimeters **Body Height:** 15.0 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 18.0 millimeters and 18.6 millimeters **Power Dissipation Rating In Watts:** 25.000 free air **Terminal Width:** 4.0 millimeters **End Application:** Box, relay 5945-spo-770540 **Mounting Hole Size:** 3.3 millimeters **Product Name:** Inavy: resistor, 25 watts; mfr: aluminum housed power resistor, type hs series **Special Features:** Power is rapidly dissipated as heat through aluminum housing to specified heatsink

Style Designator: Axial terminal (s) Shelf Life: N/a

NSN 5905-01-550-3728

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Init	<i>(</i>)+	Measure:

--

Demilitarization:

No

Fiig:

A001a0