NSN 5905-01-550-8146

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-550-8146

view Offilite at https://aerobasegroup.com/hist//0300-01-030-0140
Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
1.000
Terminal Length:
Between 0.175 inches and 0.225 inches
Shaft Diameter:
Between 0.065 inches and 0.095 inches
Shaft Length:
0.090 inches
Body Length:
Between 0.490 inches and 0.510 inches
Body Width:
Between 0.090 inches and 0.110 inches
Body Height:
Between 0.160 inches and 0.180 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
Between 0.390 inches and 0.410 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
10.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.090 inches and 0.110 inches
Power Dissipation Rating Per Section In Watts:
0.3 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Test Data Document:
589r128 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

3 pin

Terminal Type And Quantity:

NSN 5905-01-550-8146

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0