NSN 5905-01-550-8466



Noninductive Wire Wound Fixed Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-01-550-8466 **Electrical Resistance:** 1150,000 ohms **Resistance Tolerance In Percent:** -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 **Inclosure Method:** Encapsulated **Terminal Type:** Wire lead **Reactance Characteristic:** Noninductive **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Terminal Length:** 1.500 inches **Body Diameter:** Between 0.063 inches and 0.125 inches **Body Length:** Between 0.375 inches and 0.437 inches **Power Dissipation Rating In Watts:** 2.000 free air **Terminal Width:** 0.020 inches **End Application:** Tornado weapon programming unit **Style Designator:** Axial terminal each end **Test Data Document:** 81349-mil-prf-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-39007/8 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5905-01-550-8466

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39007 spec.