NSN 5905-01-552-5038

Inductive Wire Wound Fixed Resistor - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5905-01-552-5038 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -260.0/+260.0 first temp coefficient |
| Electrical Resistance: |
| 112.000 kilohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 350.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+350.0 temp range of first temp coefficient |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Tab, solder lug |
| Reactance Characteristic: |
| Noninductive |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.687 inches and 0.937 inches |
| Body Diameter: |
| 0.906 inches |
| Body Length: |
| 4.000 inches |
| Power Dissipation Rating In Watts: |
| 55.000 free air |
| Terminal Width: |
| Between 0.172 inches and 0.328 inches |
| Style Designator: |
| Radial terminal each end |
| Specification Data: |
| 81349-mil-r-26/3 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

. -

A001a0