NSN 5905-01-571-7767

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-571-7767 **Electrical Resistance:** 36.500 kilohms Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 250.0 **Inclosure Method: Encased Terminal Type:** Tab, solder lug **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.100 **Terminal Length:** Between 0.376 inches and 0.500 inches **Body Length:** Between 1.876 inches and 2.000 inches **Body Width:** Between 0.532 inches and 0.656 inches **Body Height:** Between 0.594 inches and 0.656 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** Between 1.552 inches and 1.572 inches **Power Dissipation Rating In Watts:** 10.000 free air **Terminal Width:** 0.140 inches **End Application:** RADA-RS-ET,-SEMI **Style Designator:** Axial terminal (s) **Test Data Document:** 81349-mil-prf-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-39009/1 government specification Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5905-01-571-7767

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39009 spec.