## NSN 5905-01-573-1606

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-573-1606

| 237.000 kilohms Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 30.0 millimeters Body Diameter: 2.300 inches Body Diameter: 2.300 inches Body Length: 6.3 millimeters Power Dissipation Rating In Watts: 0.250 fee air End Application: Aircraft, b-1b Product Mame: Metal film resistor Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code Shelf Life: N/a Unit Of Measure: Demilitarization: | Electrical Resistance:   |
|---|--|
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 30.0 millimeters Body Diameter: 2.300 inches Body Length: 6.3 millimeters Power Dissipation Rating In Watts: 0.250 free air End Application: Aircraft, b-1b Product Name: Metal film resistor Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code Shelf Life: N/a Unit Of Measure:   | 237.000 kilohms  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 30.0 millimeters Body Diameter: 2.300 inches Body Length: 6.3 millimeters Power Dissipation Rating In Watts: 0.250 free air End Application: Aircraft, b-1b Product Name: Metal film resistor Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code Shelf Life: N/a Unit Of Measure:   | Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 30.0 millimeters Body Diameter: 2.300 inches Body Length: 6.3 millimeters Power Dissipation Rating In Watts: 0.250 free air End Application: Aircraft, b-1b Product Name: Metal film resistor Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code Shelf Life: N/a Unit Of Measure:   | 70.0   |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Terminal Length: 30.0 millimeters Body Diameter: 2.300 inches Body Length: 6.3 millimeters Power Dissipation Rating In Watts: 0.250 free air End Application: Aircraft, b-1b Product Name: Metal film resistor Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code Shelf Life: N/a Unit Of Measure:   | Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| Encapsulated Terminal Type: Wire lead Terminal Length: 30.0 millimeters Body Diameter: 2.300 inches Body Length: 6.3 millimeters Power Dissipation Rating In Watts: 0.250 free air End Application: Aircraft, b-1b Product Name: Metal film resistor Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code Shelf Life: N/a Unit Of Measure:   | 150.0  |
| Terminal Type:  Wire lead  Terminal Length: 30.0 millimeters  Body Diameter: 2.300 inches  Body Length: 6.3 millimeters  Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name:  Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:   | Inclosure Method:  |
| Wire lead  Terminal Length: 30.0 millimeters  Body Diameter: 2.300 inches  Body Length: 6.3 millimeters  Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:  | Encapsulated   |
| Terminal Length: 30.0 millimeters  Body Diameter: 2.300 inches  Body Length: 6.3 millimeters  Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name:  Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:  | Terminal Type:   |
| 30.0 millimeters  Body Diameter: 2.300 inches  Body Length: 6.3 millimeters  Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:  | Wire lead  |
| Body Diameter:  2.300 inches  Body Length: 6.3 millimeters  Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:   | Terminal Length:   |
| 2.300 inches  Body Length: 6.3 millimeters  Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:   | 30.0 millimeters   |
| Body Length: 6.3 millimeters  Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:   | Body Diameter:   |
| Power Dissipation Rating In Watts: 0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:   | 2.300 inches   |
| Power Dissipation Rating In Watts:  0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:  | Body Length:   |
| 0.250 free air  End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:  | 6.3 millimeters  |
| End Application: Aircraft, b-1b  Product Name: Metal film resistor  Special Features: Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life: N/a  Unit Of Measure:  | Power Dissipation Rating In Watts:   |
| Aircraft, b-1b  Product Name:  Metal film resistor  Special Features:  Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life:  N/a  Unit Of Measure:  | 0.250 free air   |
| Product Name:  Metal film resistor  Special Features:  Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life:  N/a  Unit Of Measure:  | End Application:   |
| Metal film resistor  Special Features:  Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life:  N/a  Unit Of Measure:   | Aircraft, b-1b   |
| Special Features:  Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life:  N/a  Unit Of Measure:  | Product Name:  |
| Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life:  N/a  Unit Of Measure:   | Metal film resistor  |
| performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code  Shelf Life:  N/a  Unit Of Measure:  | Special Features:  |
| Shelf Life: N/a Unit Of Measure:  | Resistance tolerance in percent: plus or minus 1 percent, temp coefficient of resistance in ppm per degrees celcius: plus or minus 50, |
| N/a<br>Unit Of Measure:<br>   | performance reliability: low t.C.R. And noise, high reliability, marking: 5 color code   |
| Unit Of Measure:  | Shelf Life:  |
| <del></del>   | N/a  |
|   | Unit Of Measure:   |
| Demilitarization:   |  |
|   | Demilitarization:  |
| No  | No   |
| Fiig:   | Fiig:  |
| A001a0  | A001a0   |
|   |  |