NSN 5905-01-576-2009

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-576-2009 **Section Quantity:** 3 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established Flat Height: 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.343 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 2.5 kilohms all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 all sections **Special Features:** 70f series potentiometer, 3-section; cermet, 2.5k ohm linear taper, 2.R5k ohm lineartaper with type 1003/dpst switch, solder-lug terminals; standard marking with mfr p/n l24612 and catalog reference and date/lot number **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5905-01-576-2009

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0