## NSN 5905-01-576-2020

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-576-2020 **Section Quantity:** 3 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.343 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Screw Thread Diameter:** 0.375 inches **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 500.0 ohms all sections **Power Dissipation Rating Per Section In Watts:** 2.0 free air all sections **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 all sections **Special Features:** 70f series potentiometer, 3-section; cermet, 500 ohm linear taper with type 1003/dpst switch; 6 solder-lug terminals; standard marking with mfr p/n l23693 and catalog reference and date/lot number Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 5905-01-576-2020

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0