## NSN 5905-01-580-4620

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-580-4620 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.094 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** Between 0.344 inches and 0.390 inches **Body Length:** 1.266 inches **Shaft Style:** Round, slotted **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 100.0 kilohms all sections **Rotary Actuator Travel In Angular Deg:** Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 all sections **Power Dissipation Rating Per Section In Watts:** 

0.5 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 all sections

## NSN 5905-01-580-4620

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator T	ravel (	Control	Feature:
------------	---------	---------	----------

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

**Terminal Type And Quantity:** 

6 tab, solder lug

,

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A002a0