NSN 5905-01-582-0558

Film Fixed Resistor - Page 1 of 1

Mil-prf-55182 spec.



View Online at https://aerobasegroup.com/nsn/5905-01-582-0558

FLATALBUTA.
Electrical Resistance:
2.700 kilohms each resistor
Resistance Tolerance In Percent:
-1.000/+1.000 each resistor
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+175.0 temp range of first temp coefficient
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.250 inches
Body Diameter:
0.065 inches
Body Length:
0.150 inches
Power Dissipation Rating In Watts:
0.050 free air
End Application:
Rhwr lbrrx, hbrrx and 30ff frfhs + head amp and zeus rf/ if converter
Special Features:
Item meets specification mil-prf-55182/7; temperature coeffecient of resistance in ppm per degrees celius -50deg c to 50.0deg c
Style Designator:
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0
Mil-std (military Standard):