NSN 5905-01-583-1988

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-583-1988

| Electrical Resistance: |
|---|
| 130.000 ohms each resistor |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 each resistor |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 175.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.001 |
| Terminal Length: |
| Between 0.984 inches and 1.516 inches |
| Body Diameter: |
| Between 0.060 inches and 0.080 inches |
| Body Length: |
| Between 0.130 inches and 0.170 inches |
| Power Dissipation Rating In Watts: |
| 0.100 free air |
| Terminal Width: |
| 0.016 inches |
| End Application: |
| Rhwr head amp and zeus rf/if converter |
| Product Name: |
| Cage: metal film resistors, military/established reliability, mil-prf-55182 qualified, type rn (/rnr) , characteristics j, h, k |
| Special Features: |
| Packaging: tin/lead tape/reel |
| Style Designator: |
| Axial terminal each end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |

NSN 5905-01-583-1988

Film Fixed Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-55182 spec.