NSN 5905-01-585-7744

Film Fixed Chip Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-585-7744 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -100.0/+100.0 first temp coefficient |
| Electrical Resistance: |
| 18.200 kilohms each resistor |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 each resistor |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 150.0 |
| Inclosure Method: |
| Uninclosed |
| Terminal Type: |
| Terminal type per body style |
| Reliability Indicator: |
| Not established |
| Body Length: |
| 2.0 millimeters |
| Body Width: |
| 1.3 millimeters |
| Body Height: |
| 0.4 millimeters |
| Power Dissipation Rating In Watts: |
| 0.150 free air |
| End Application: |
| I-cap ii peculiar aircraft (ea-6b) |
| Product Name: |
| Inavy: resistor fxd film; drawing: resistor, chip, fixed film, moisture resistant, miltary, style 0705 |
| Special Features: |
| Has b type terminals iaw mil-prf-55342 |
| Style Designator: |
| Termination pad each end |
| Supplementary Features: |
| Must be purchased to dscc pin (part number) to assure all performance reqs and tests are met |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A001a0

NSN 5905-01-585-7744

Film Fixed Chip Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-55342 spec.