## NSN 5905-01-585-9028

Film Fixed Chip Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-585-9028   |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
| -100.0/+100.0 first temp coefficient  |
| Electrical Resistance:  |
| 1.000 kilohms each resistor   |
| Resistance Tolerance In Percent:  |
| -2.000/+2.000 each resistor   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 70.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 150.0   |
| Inclosure Method:   |
| Uninclosed  |
| Terminal Type:  |
| Terminal type per body style  |
| Reliability Indicator:  |
| Not established   |
| Body Length:  |
| 3.9 millimeters   |
| Body Width:   |
| 1.3 millimeters   |
| Body Height:  |
| 0.4 millimeters   |
| Power Dissipation Rating In Watts:  |
| 0.150 free air  |
| End Application:  |
| I-cap ii peculiar aircraft (ea-6b)  |
| Product Name:   |
| Inavy: resistor fxd film; drawing: resistor, chip, fixed film, moisture resistant, military, style 1505 |
| Special Features:   |
| Has b type terminals iaw mil-prf-55342  |
| Style Designator:   |
| Termination pad each end  |
| Supplementary Features:   |
| Must be purchased to dscc pin (part number) to assure all performance reqs and tests are met            |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |

Fiig:

A001a0

## NSN 5905-01-585-9028

Film Fixed Chip Resistor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-55342 spec.