NSN 5905-01-587-6291

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-587-6291 **Electrical Resistance:** 10.000 ohms each resistor **Resistance Tolerance In Percent:** -1.000/+1.000 each resistor **Heat Sink Material:** Aluminum alloy **Heat Sink Length:** 9.000 inches **Heat Sink Width:** 7.000 inches **Heat Sink Height:** 2.000 inches **Heat Sink Thickness:** 0.060 inches Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 **Tempurature Range Of Tempurature Coefficient In Deg Celsius:** -55.0/+275.0 temp range of first temp coefficient **Inclosure Method:** Encapsulated **Terminal Type:** Threaded stud **Reactance Characteristic:** Inductive **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 4.500 inches **Body Width:** 2.125 inches **Body Height:** 2.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 3.000 inches **Power Dissipation Rating In Watts:** 75.000 free air

End Application:

Rectifier

NSN 5905-01-587-6291

Mil-prf-18546 spec.

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Mounting Hole Size:
0.188 inches
Product Name:
Wirewound resistors, military, mil-prf-18546 qualified, type re, aluminum housed, chassis mount
Special Features:
Meets milr18546-2
Style Designator:
Axial terminal (s)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0
Mil-std (military Standard):