NSN 5905-01-591-7360

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-591-7360

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.325 inches |
| Shaft Diameter: |
| 0.096 inches |
| Shaft Length: |
| 0.060 inches |
| Body Length: |
| 0.395 inches |
| Body Width: |
| 0.190 inches |
| Body Height: |
| 0.375 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Left adjacent side two rows |
| Mounting Method: |
| Terminal |
| Center To Center Distance Between Terminal Rows: |
| 0.100 inches |
| Electrical Resistance Per Section: |
| 50.0 percent, rated amperes c and better flooring |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 7th secondary quality |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Product Name: |
| 3296 - 3/8" square trimpot trimming potentiometer, rohs compliant |
| Special Features: |

opeoiai i cataico

Rohs compliant; 100% tin-plated terminals; packaging: tube

NSN 5905-01-591-7360

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A002a0