Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-593-0981

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### First Flat Length:

0.716 inches

#### Flat Height:

0.216 inches

#### Body Diameter:

0.906 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

## 0.875 inches

## Mounting Bushing Length:

0.375 inches

### **Body Length:**

0.453 inches

### Shaft Style:

Round, flatted

#### Actuator Type:

Single shaft

#### End Application:

C130 amp cmb

#### Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

5.0 kilohms single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section



## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0