## NSN 5905-01-593-8822

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-593-8822 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.344 inches Flat Height: 0.219 inches **Body Diameter:** 3.190 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.780 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **End Application:** Conflagration station no.1 710038101; conflag station no.4; conflag station no.3; conflag station no.2 **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Radially positioned over less than half the circumference

### **Mounting Method:**

Standard bushing

#### **Electrical Resistance Per Section:**

350.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

300.0

#### **Power Dissipation Rating Per Section In Watts:**

100.0 heat sink single section

# NSN 5905-01-593-8822

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



### Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

**Product Name:** 

Inavy: rheostat, dimmer

**Terminal Type And Quantity:** 

3 tab, solder lug

**Specification Data:** 

81349-mil-prf-22/8 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0

Mil-std (military Standard):

Mil-prf-22 spec.