## NSN 5905-01-596-1552

Film Fixed Resistor - Page 1 of 1



| view Online at https://aerobasegroup.com/hsh/5905-01-596-1552  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -100.0/+100.0 first temp coefficient   |
| Electrical Resistance:   |
| 16.900 kilohms each resistor   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000 each resistor  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 175.0  |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.310 inches   |
| Body Length:   |
| 0.800 inches   |
| Power Dissipation Rating In Watts:   |
| 2.160 free air   |
| End Application:   |
| Wire rope assembly; fixture assembly; cass/otps  |
| Special Features:  |
| Rohs compliant: coating: blue flame-retardant epoxy; element: high termp fired cermet film; core: high puri type 96 pct alumina; |
| termination: solder-coated copper  |
| Style Designator:  |
| Axial terminal each end  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |

A001a0