# NSN 5905-01-606-9928

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-606-9928

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-25.0 to 25.0

## **Electrical Resistance:**

150.0 ohms

## **Resistance Tolerance In Percent:**

-0.100 to 0.100

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.00

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.00

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 175.0

### **Inclosure Method:**

Encapsulated

## **Terminal Type:**

Wire lead

## Mil-std-1276 Wire Lead Type Designator:

```
С
```

## **Reliability Indicator:**

Established

## Reliability Failure Rate Level In Percent:

0.01

### **Terminal Length:**

1.500 inches

## **Body Diameter:**

Between 0.165 inches and 0.195 inches

### **Body Length:**

0.687 inches

**Power Dissipation Rating In Watts:** 

0.250 free air

## End Application:

B-1

# Product Name:

Metal film resistors, military/established reliability, mil-prf-55182 qualified, precision, type rnc, characteristics j, h, k

# **Special Features:**

Wire lead length: 1.50in

# Style Designator:

Axial terminal each end

## Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5905-01-606-9928

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.

