NSN 5905-01-608-5709

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-608-5709 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -50.0 to 50.0 |
| Electrical Resistance: |
| 2.200 ohms |
| Resistance Tolerance In Percent: |
| -1.000 to 1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.00 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 275.0 |
| Inclosure Method: |
| Encased |
| Terminal Type: |
| Tab, solder lug |
| Reactance Characteristic: |
| Inductive |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.010 |
| Terminal Length: |
| Between 0.204 inches and 0.328 inches |
| Body Length: |
| Between 0.538 inches and 0.662 inches |
| Body Width: |
| Between 0.272 inches and 0.396 inches |
| Body Height: |
| Between 0.289 inches and 0.351 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 0.434 inches and 0.454 inches |
| Power Dissipation Rating In Watts: |
| 3.000 free air |
| Err Default: |
| 0.085 inches |
| End Application: |
| B1 |
| Mounting Hole Size: |
| Between 0.088 inches and 0.098 inches |
| |

Style Designator:

Axial terminal (s)

NSN 5905-01-608-5709

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A001a0