

View Online at <https://aerobasegroup.com/nsn/5905-01-609-7402>

**Section Quantity:**

3

**Body Style:**

Rectangular

**Overall Length:**

1.308 inches

**Overall Height:**

0.19 inches

**Overall Width:**

0.815 inches

**Mounting Hole Diameter:**

0.093 inches

**Mounting Bushing Length:**

0.5 inches

**Body Length:**

1.25 inches

**Body Width:**

0.315 inches

**Body Height:**

0.19 inches

**Mounting Hole/stud Circle Diameter:**

0.028 inches

**Shaft Style:**

Round, threaded

**Actuator Type:**

Single shaft

**Center To Center Distance Between Terminals:**

0.300 inches

**Distance Between Mounting Hole Centers:**

0.1 inches

**End Application:**

2350-01-578-8412, tank, combat, full tracked

**Lateral Distance Between Mounting Hole Centers:**

0.03 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Unthreaded hole

**Center To Center Distance Between Terminal Rows:**

0.1 inches

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.300 inches

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0 to 100.0 all sections

**Actuator Travel Control Feature:**

Clutch

**Product Name:**

3059-trimpot, trimming potentiometer

**Special Features:**

Adjustability voltage + or - .01%, resistance + or - .05%, effective travel 22 turns nom, power rating at 70 degrees c 1.0 watt, power rating at 150 degrees c 0 watt, temperature range -55 degrees c to 150 degrees c, rotational life 200 cycles, weight 0.1 oz. Terminals solder printed circuit pins, resistance (ohms)5000per mil-prf-22097.

**Terminal Type And Quantity:**

3 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0

**Mil-std (military Standard):**

Mil-prf-22097 spec.