## NSN 5905-01-615-3199

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-615-3199

Townselves Coefficient Of Projectors In Prog Day Day Onlying
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0 to 20.0
Electrical Resistance:
800.0 ohms
Resistance Tolerance In Percent:
-1.0 to 1.0
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
250.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reactance Characteristic:
Inductive
Mil-std-1276 Wire Lead Type Designator:
N-1
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.2
Terminal Length:
1.50 inches
Body Diameter:
0.094 inches
Body Length:
0.406 inches
Power Dissipation Rating In Watts:
2.0 free air
Err Default:
0.020 inches
Special Features:
High temperature silicone coated, completed weld construction, qualified to mil-prf-39007
Style Designator:
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
TNO

## NSN 5905-01-615-3199

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39007 spec.