NSN 5905-01-615-7665

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-615-7665

Townsertons Operfficient Of Presistance In President
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-50.0 to 50.0
Electrical Resistance:
1.2 ohms
Resistance Tolerance In Percent:
-1.0 to 1.0
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
250.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reactance Characteristic:
Inductive
Mil-std-1276 Wire Lead Type Designator:
N-1
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.2
Terminal Length:
1.50 inches
Body Diameter:
0.187 inches
Body Length:
0.560 inches
Power Dissipation Rating In Watts:
3.0 free air
Err Default:
0.032 inches
Special Features:
High temperature silicone coated, complete welded construction, qualified to mil-prf-39007
Style Designator:
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

NSN 5905-01-615-7665

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39007 spec.