NSN 5905-01-615-8632

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-615-8632

Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Shaft Diameter:
0.093 inches
Shaft Length:
0.060 inches
Body Length:
0.750 inches
Body Width:
0.190 inches
Body Height:
0.250 inches
Shaft Style:
Round, cross slotted
Actuator Type:
Single shaft
Maximum Running Torque:
5.0 inch-ounces
Center To Center Distance Between Terminals:
0.500 inches
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
500000.0 ohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Special Features:

opeoidi i catalos

Zink plated terminals

NSN 5905-01-615-8632

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



reminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0