NSN 5905-01-616-8276

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-616-8276

Section Oceantitus
Section Quantity:
1 Parts Chales
Body Style:
Rectangular
Reliability Indicator: Not established
Terminal Length: 0.180 inches
Shaft Diameter:
0.0090 inches
Shaft Length:
0.060 inches
Body Length:
0.375 inches
Body Width:
0.375 inches
Body Height:
0.245 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Mounting Facility Quantity:
3
Terminal Location:
Right adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
2.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section

NSN 5905-01-616-8276

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Product Name:
Model 68 3/8" square cermet trimming potentiometer
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: