NSN 5905-01-622-7674

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-622-7674

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
0.249 inches
Shaft Length:
0.470 inches
Mounting Stud Length:
0.250 inches
Mounting Bushing Length:
0.342 inches
Body Length:
0.750 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
1
Terminal Location:
Right adjacent side single row
Mounting Method:
Threaded stud
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
30.0
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 single section

NSN 5905-01-622-7674

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0