NSN 5905-01-624-8719

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-624-8719

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.860 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.499 inches
Mounting Stud Length:
0.250 inches
Mounting Bushing Length:
0.313 inches
Body Length:
0.480 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
End Application:
C5m amp se
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
1
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded stud
Electrical Resistance Per Section:
10.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:

-3.0 to 3.0 single section

NSN 5905-01-624-8719

Precision Wire Wound Variable Resistor - Page 2 of 2



Precious Material And Location:
Terminal surface gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0