NSN 5905-01-624-9642

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-624-9642

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
1.563 inches
Flat Height:
0.344 inches
Body Diameter:
12.0 inches
Shaft Diameter:
0.375 inches
Shaft Length:
2.0 inches
Mounting Bushing Length:
1.25 inches
Body Length:
3.0 inches
Shaft Style:
Round, flatted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
20.0
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
2.500 ohms single section
Power Dissipation Rating Per Section In Watts:
1000.0 free air single section
Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

NSN 5905-01-624-9642

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0