## NSN 5905-01-625-6436

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-625-6436

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

-20.0 to 20.0	
Electrical Resistance:	
16.0 ohms	
Resistance Tolerance In Percent:	
-1.0 to 1.0	
Ambient Tempurature In Deg Celsius At Full Rated Power:	
25.0	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:	
250.0	
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	
-50.0 to 250.0	
Inclosure Method:	
Encapsulated	
Terminal Type:	
Wire lead	
Reactance Characteristic:	
Inductive	
Reliability Indicator:	
Not established	
Terminal Length:	
0.438 inches	
Body Diameter:	
0.630 inches	
Body Length:	
2.781 inches	
Body Width:	
0.630 inches	
Body Height:	
0.610 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:	
1.968 inches	
Power Dissipation Rating In Watts:	
20.0 free air	
Mounting Hole Size:	
0.125 inches	
Product Name:	
Wirewound resistor, industrial power, aluminum housed, chassis mount	
Special Features:	
Lea (pb) -free; card pack; element: copper-nickel alloy; core: ceramic, steatite or alumina; encapsulant: silicone molded construction;	
housing: aluminum with hard anodic coating; end caps: stainless steel	
Style Designator:	
Radial terminals	

## NSN 5905-01-625-6436

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0