NSN 5905-01-626-5468

Film Fixed Chip Resistor - Page 1 of 2



Timit inca emp redictor it ago i of 2					
View Online at https://aerobasegroup.com/nsn/5905-01-626-5468					
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:					
-100.0 to 100.0					
Electrical Resistance:					
49.9 ohms					
Resistance Tolerance In Percent:					
-1.0 to 1.0					
Ambient Tempurature In Deg Celsius At Full Rated Power:					
70.0					
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power					
150.0					
Tempurature Range Of Tempurature Coefficient In Deg Celsius:					
-65.0 to 150.0					
Inclosure Method:					
Encapsulated					
Terminal Type:					
Wrap around					
Reliability Indicator:					

Established

Reliability Failure Rate Level In Percent:

0.01

Terminal Length:

Between 0.093 inches and 0.103 inches

Body Length:

Between 0.191 inches and 0.218 inches

Body Width:

Between 0.093 inches and 0.103 inches

Body Height:

Between 0.015 inches and 0.025 inches

Power Dissipation Rating In Watts:

0.8 free air

Unable To Decode:

Between 0.015 inches and 0.025 inches

End Application:

Apx113

Product Name:

M55342/08 rm2010 thick film chip resistor

Style Designator:

Termination pad each end

Specification Data:

81349-mil-prf-55342/08 government specification

Shelf Life:

N/a

NSN 5905-01-626-5468

Film Fixed Chip Resistor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55342 spec.