## NSN 5905-01-627-0692

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-627-0692

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
liilength:
1.328 inches
Terminal Length:
0.475 inches
Body Diameter:
0.500 inches
Mounting Hole Diameter:
0.265 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.453 inches
liidiameter:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
5.0 inch-ounces
Maximum Running Torque:
5.0 inch-ounces
Nonturn Device Location:
At 4'30 oclock and at 10'30 oclock
Nonturn Device Radius:
0.249 inches
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged

## NSN 5905-01-627-0692

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



End Application:
2355-01-560-2306
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
1
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0 to 150.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Product Name:
Potentometer 5k
Special Features:
Trailing I in p/n indicates rohs compliance
Terminal Type And Quantity:
3 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-01-627-0692

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0