## NSN 5905-01-627-8996

-20.0 to 20.0

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-627-8996

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

Electrical Resistance:
56.0 ohms
Resistance Tolerance In Percent:
-1.0 to 1.0
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
250.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 250.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reactance Characteristic:
Inductive
Reliability Indicator:
Not established
Terminal Length:
0.312 inches
Body Diameter:
0.420 inches
Body Length:
0.750 inches
Body Width:
0.420 inches
Body Height:
0.390 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.562 inches
Power Dissipation Rating In Watts:
10.0 free air
Mounting Hole Size:
0.094 inches
Product Name:
Wirewound resistor, industrial power, aluminum housed, chassis mount
Special Features:
Element: copper-nickel alloy; core: ceramic, steatite or alumina; encapsulant: silicone molded construction; housing: alumiminum with
hard anodic coating; end caps: stainless steel
Style Designator:
Axial terminal (s)

## NSN 5905-01-627-8996

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Shelf	l ife·
Olicii	LIIC.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0